

Design ID: **Z42B**

Description: **16Gb DDR4 SDRAM**

Marketing device name(s): **MT40A4G4SA, MT40A2G8SA, MT40A1G16TB, MT40A4G4Z42B, MT40A2G8Z42B, MT40A1G16Z42B**

Valid speed grades **DDR4-1600, DDR4-1866, DDR4-2133, DDR4-2666, DDR4-2400, DDR4-2933, DDR4-3200**

Zip filename: **z42b_ibis.zip**

IBIS filename (Version 5.0): **z42b.ibs, z42b_it.ibs** File rev: **2.4.2**

HSPICE filename: **N/A** File rev: **N/A**

Die revision: **F**

Date: **November 29, 2022**

For support contact your local Micron FAE/Sales contacts
(more information at <https://www.micron.com/support/sales-network>)

Device Parameterscd.

VDDQ Slow: **1.14V** Typical: **1.20V** Fast: **1.26V**

VDD Slow: **1.14V** Typical: **1.20V** Fast: **1.26V**

Junction Temperature (Commercial) Slow: **110C** Typical: **50C** Fast: **0C**

Junction Temperature (Industrial) Slow: **110C** Typical: **50C** Fast: **-40C**

VDDQ/VSSQ Decoupling Capacitance (Approximate value at 10MHz) – Full Die: **7.75nF**

Included in HSPICE DQ/DQS/DM models? **Yes** Amount per DQ/DQS/DM model: **352pF**

Included in IBIS DQ/DQS/DM models? **No, must be included with separate Spice subcircuit (.ckt files) found in the zip file.**

VDDQ/VSSQ Decoupling Capacitance ESR – Full Die: **55mohm**

VDDQ/VSSQ Decoupling Capacitance ESR – per DQ model: **1.2ohm**

IBIS Quality Summary

1. ☒ Include the IBIS Quality Specification 2.0 Overall IBIS Quality level. For details on IBIS Quality, reference the quality specification and quality checklist on IBIS quality webpage http://www.ibis.org/quality_wip/checklist.html.

Overall IBIS Quality Level: IQ3MSX

Exceptions: V-t length in Version 5.0 model is excessive due to inclusion of [Composite Current] I-t data.


2. ☒ Include the filename of the IBIS Quality Checklist that accompanies this report.

Filename for Version 5.0 file: z42b_ibis_quality_checklist.xls


IBIS Model Correlation: datasheet

1. ☒ For Output or I/O model compare datasheet IOH/IOL data with IBIS pullup/pulldown data.

- a. Model name: **DQ_34_3200**
 i. Pullup I-V versus JEDEC specification




ii. Pulldown I-V versus JEDEC specification




b. Model name: **DQ_40_3200**

i. Pullup I-V versus **JEDEC** specification




ii. Pulldown I-V versus JEDEC specification




c. Model name: **DQ_48_3200**

i. Pullup I-V versus **JEDEC** specification



ii. Pulldown I-V versus JEDEC specification



1. ☒ Compare C_comp with datasheet Input Capacitance. Provide C_comp comparison table for all models and for all package combinations (i.e. x4, x8 and x16).

Component name:

MT40A4G4SA, MT40A2G8SA

Signal	IBIS die min [pF]	IBIS die max [pF]	Spec tot min [pF]	Spec tot max [pF]
DQ	0.610	0.710	0.70	1.40
INPUT	0.240	0.340	0.20	0.70
CLK	0.292	0.392	0.20	0.70
RESET	0.250	0.350	0.20	0.70
ALERT	0.550	0.650	0.50	1.50

2. ☒ Compare package impedance and time delay with datasheet specifications. Provide comparison table for all package combinations.

Component name:

MT40A4G4SA, MT40A2G8SA

Signal	Z pkg IBIS min [Ω]	Z pkg IBIS max [Ω]	Z pkg SPEC min [Ω]	Z pkg SPEC max [Ω]	Td pkg IBIS min [ps]	Td pkg IBIS max [ps]	Td pkg SPEC min [ps]	Td pkg SPEC max [ps]
IO	54.5	64.0	45	85	31.6	36.0	14	40
ADD/CMD	68.8	73.6	50	90	27.7	35.5	14	40
CLK	60.1	62.3	50	90	31.4	32.3	14	42
ALERT	58.6	58.6	40	100	36.2	36.2	20	55


3. ☒ If slew rate specifications (rise/fall slew) are available from the datasheet, complete Spice simulations to generate slew rate data and provide a comparison table.

Model	IBIS slew rate RISE [V/ns] typ	IBIS slew rate RISE [V/ns] min	IBIS slew rate RISE [V/ns] max	SPEC slew rate RISE [V/ns] min	SPEC slew rate RISE [V/ns] max
DQ_34_3200	10.14	7.39	13.33	4.0	9.0
DQ_40_3200	9.62	7.06	12.62	4.0	9.0
DQ_48_3200	8.66	6.35	11.35	4.0	9.0


Model	IBIS slew rate FALL [V/ns] typ	IBIS slew rate FALL [V/ns] min	IBIS slew rate FALL [V/ns] max	SPEC slew rate FALL [V/ns] min	SPEC slew rate FALL [V/ns] max
DQ_34_3200	10.07	7.48	13.13	4.0	9.0
DQ_40_3200	9.59	7.18	12.42	4.0	9.0
DQ_48_3200	8.65	6.68	11.13	4.0	9.0

4. ☒ Compare ODT data with datasheet.


a. ODT34




b. ODT40




c. ODT48




d. ODT60




e. ODT80



f. ODT120




g. ODT240




IBIS Model Correlation: IBIS vs Spice (Driver-Receiver)

1. ☒ For all Output or I/O models, run Spice transient simulations using encrypted netlists and the IBIS model (b-element).
 - a. ☒ Use the setup and node naming conventions shown below for the IBIS and Spice files.
Update the setup diagram if it is different. Indicate the version of Spice simulator used for simulations: **HSPICE S-2021.09**
 - b. ☒ Run simulations for all corners cases and at fastest speed grades, testing ODT models as loads when applicable


SETUP:




i. **DQ_34_3200** driving **DQ_34_3200**




ii. DQ_34_3200 driving DQ_IN_ODT34_3200




iii. DQ_34_3200 driving DQ_IN_ODT40_3200




iv. DQ_34_3200 driving DQ_IN_ODT48_3200




v. DQ_34_3200 driving DQ_IN_ODT60_3200




vi. DQ_34_3200 driving DQ_IN_ODT80_3200




vii. DQ_34_3200 driving DQ_IN_ODT120_3200




viii. DQ_34_3200 driving DQ_IN_ODT240_3200



ix. DQ_40_3200 driving DQ_IN_ODT60_3200




x. DQ_48_3200 driving DQ_IN_ODT60_3200



IBIS Model Correlation: IBIS vs Spice (Driver Load)

1. ☒ For all Output or I/O IBIS Version 5.0 power-aware models, run Spice transient simulations using encrypted netlists and the IBIS model (b-element) with a non-ideal power supply connection.
 - a. ☒ Use the setup and node naming conventions shown in Setup B below for the IBIS and Spice files. Update the setup diagram if it is different. Indicate the version of Spice simulator used for simulations: **HSPICE S-2021.09**
 - b. ☒ Run simulations for all corner cases and at fastest speed grades

SETUP B:




Test Load Values

Z0	=	50 Ω
Td	=	200 ps
Cload	=	5 pF
Rload	=	50 Ω
VTT	=	VDDQ


Package Model used for correlation

Lpkg	PAD	BALL	1.25n	0.25
Lpkg_vccq	vccq_die	vccq_ball	1.25n	0.25
Lpkg_vssq	vssq_die	vssq_ball	0.10n	0.05
K1	Lpkg_vccq	Lpkg_vssq	0.20	
K2	Lpkg	Lpkg_vccq	0.40	
K3	Lpkg	Lpkg_vssq	0.20	
Cpkg_vccq	BALL	vccq_ball	0.20p	
Cpkg_vssq	BALL	vssq_ball	0.20p	
Cpkg_vccq_vssq	vccq_ball	vssq_ball	0.40p	


i. DQ_34_3200



ii. DQ_40_3200



iii. DQ_48_3200



Comments

1. IBIS model may not reflect current speed grade availability.
2. Slew rate is based on HSPICE simulation with a 50ohm load to VDDQ. This includes simple package parasitics for pin and power/gnd nets

Document Revision History

- Rev 2.4.2 - Date **November 29, 2022**
a. IBIS revision (Version 5.0) **2.4.2**
- Rev 2.4.1 - Date **August 26, 2022**
b. IBIS revision (Version 5.0) **2.4.1**
- Rev 2.4 - Date **May 27, 2022**
c. IBIS revision (Version 5.0) **2.4**
- Rev 2.3 - Date **May 11, 2022**
a. IBIS revision (Version 5.0) **2.3**
- Rev 2.2 - Date **May 6, 2022**
b. IBIS revision (Version 5.0) **2.2**
- Rev 2.1 - Date **November 2, 2021**
d. IBIS revision (Version 5.0) **2.1**