ONFI Technical Errata

Errata ID	**002**
Affected Spec Ver.	**ONFI 2.0**
Corrected Spec Ver.	

Submission info

Name	Company	Date
Michael Abraham	Micron	2/22/2008

Description of the specification technical flaw (add space as needed)

The tRCBSY/tPCBSY typical times listed in the ONFI specification vary between SLC and MLC devices and particularly for MLC devices are greater than the typical times listed.

Description of the correction

Original view of Table 15:

Parameter	Typical	Maximum
tIEBSY	500 ns	tBERS
tIPBSY	500 ns	tPROG
tPCBSY	3 µs	tPROG
tRCBSY	3 µs	tR

Table 15 Cache and Interleave Short Busy Times

Modify Table 15 as shown:

Parameter	Typical	Maximum
tIEBSY	500 ns	tBERS
tIPBSY	500 ns	tPROG
tPCBSY	3 µs	tPROG
tRCBSY	3 µs	tR
NOTE: 1. Typical times for tPCBSY and tRCBSY are the recommended interval at which the host should consider polling status. Device busy time may be longer than the typical value.		

Table 1 Cache and Interleave Short Busy Times

Disposition log

2/22/2008	Erratum captured.
4/15/2008	Erratum ratified.

Technical input submitted to the ONFI Workgroup is subject to the terms of the ONFI contributor's agreement.