ONFI Technical Errata

Errata ID	**022**
Affected Spec Ver.	**ONFI 3.0, 3.1, 3.2, 4.0**
Corrected Spec Ver.	

Submission info

Name	Company	Date
Terry Grunzke	Micron	10/17/16

This errata updates Absolute Maximum DC ratings to align with discussions in JTG.

Description of the specification change

Modify Section 2.9 “Absolute Maximum DC ratings” Table 6 shown below:

Parameter	Symbol	Rating	Units
VPP Supply Voltage	V_{PP}	-0.6 to +16	V
Vcc = 3.3V and VccQ = 3.3V nominal			
Vcc Supply Voltage	V_{CC}	-0.6 to +4.6	V
Voltage Input	V_{IN}	-0.6 to +4.6	
VccQ Supply Voltage	V_{CCQ}	-0.6 to +4.6	
Vcc = 3.3V and VccQ = 1.8V nominal			
Vcc Supply Voltage	V_{CC}	-0.6 to +4.6	V
Voltage Input	V_{IN}	~~-0.45~~ -0.2 to +2.4	
VccQ Supply Voltage	V_{CCQ}	~~-0.45~~ -0.2 to +2.4	
Vcc = 3.3V and VccQ = 1.2V nominal			
Vcc Supply Voltage	V_{CC}	-0.6 to +4.6	V
Voltage Input	V_{IN}	~~-0.4~~ -0.2 to +1.5	
VccQ Supply Voltage	V_{CCQ}	~~-0.4~~ -0.2 to +1.5	
Vcc = 1.8V and VccQ = 1.8V nominal			
Vcc Supply Voltage	V_{CC}	~~-0.45~~ -0.2 to +2.4	V
Voltage Input	V_{IN}	~~-0.45~~ -0.2 to +2.4	
VccQ Supply Voltage	V_{CCQ}	~~-0.45~~ -0.2 to +2.4	

Table 6 Absolute maximum DC ratings

Disposition log

10/17/2016	Erratum captured.

Technical input submitted to the ONFI Workgroup is subject to the terms of the ONFI contributor's agreement.